Distribution Cable (Indoor/Outdoor Cable)




Apollo Technology Fibre Optic distribution cable (Indoor/Outdoor Cable) uses top quality materials to guarantee excellent results across a wide array of deployments. there are a number of number of different uses for these cables including: indoor, inside building buildings and FTTD.

- It can supply bandwidth, transmission speech, data, TV and video
- Characteristic: small diameter, lightweight and flexible so it is easy to install, maintain and manage

(Characteristic)

*Excellent stripping performance of tight buffer Fibre

*Small cable diameter and bending radius allow it to be easily installed in small places



(Geometrical Characteristics)

| Distribution Cable Type | 2 | 4 | 6 | 8 | 12 | 24 | 48 |
|----------------------------------|--------|------|------|------|------|------|-------|
| Distribution Cable Diameter(mm) | 5.00 | 5.10 | 5.30 | 6.00 | 6.60 | 8.50 | 10.50 |
| Distribution Cable Weight(kg/km) | 20 | 20 | 22 | 25 | 28 | 50 | |
| TBF Diameter(μm) | 900±50 | | | | | | |

(Mechanical Characteristics)

| Max Load(N |) Long Term | 130 | 130 | 130 | 130 | 130 | 200 |
|------------|-------------|--------------------------|-----|-----|-----|-----|-----|
| | Short Term | 440 | 440 | 440 | 440 | 440 | 660 |
| Bending | Dynamic | 20×D (D: Cable Diameter) | | | | | |
| Radius(CM) | Static | 10×D (D: Cable Diameter) | | | | | |

| (Fibre) | |
|-------------------------------------|---------------------------|
| Fibre Type(core/cladding dimension) | 8.3/125, 50/125, 62.5/125 |



| (Transmission Characteristics) | | | | | | |
|-------------------------------------|---------------|--------------|--------------|--|--|--|
| | SMF | 50/125 | 62.5/125 | | | |
| | 1310/1550(nm) | 850/1300(nm) | 850/1300(nm) | | | |
| (dB/km) Max Attenuation(dB/ km) | 0.45/0.30 | 3.5/1.5 | 3.5/1.5 | | | |
| (dB/km) AVG. Attenuation(dB/ km) | 0.40/0.25 | 3.0/1.0 | 3.0/1.0 | | | |
| (MHz•km) Min Bandwidth(MHz•km) | | 400/400 | 160/500 | | | |

(Environmental Characteristics)

(Storage Operating Temperature)

-20°C~+60°C

Ordering information:

Singlemode:

- SM4- 4 Core Singlemode Indoor/Outdoor Cable
- SM6- 6 Core Singlemode Indoor/Outdoor Cable
- SM8- 8 Core Singlemode Indoor/Outdoor Cable
- SM12- 12Core Singlemode Indoor/Outdoor Cable
- SM24- 24 Core Singlemode Indoor/Outdoor Cable

OM3 50 Micron:

- OM36- 6 Core 50 micron OM3 Indoor/Outdoor Cable
- OM312- 12 Core 50 micron OM3 Indoor/Outdoor Cable
- OM324- 24 Core 50 micron OM3 Indoor/Outdoor Cable

OM4 50 Micron:

- OM46: 6 Core 50 micron OM4 Indoor/Outdoor Cable
- OM412: 12 Core 50 micron OM4 Indoor/Outdoor Cable
- OM424: 24 Core 50 micron OM3 Indoor/Outdoor Cable